



E-Trade General Merchandizing

Rm 718 Cityland10 Tower 2, 154 HV Dela Costa Salcedo Village, Makati

TEL: 468-3832, 892-7415 Fax 893-4903 MOBILE: 0917-8370211

email: evangeline_g71@yahoo.com

LED Spotlight

Product No	Base	LED Q'ty	Input voltage(V)	Color	Color temperature Wave length(nm)λ	Power(W)	Output Comparabl e	lumens	
TP-FMR16-24LED-001 	MR16	24 LEDs	AC12V	Warm White	2600-3700K	1.2W	25W	60 Lumens	
				Daylight White	5000-7000K		25W	60 Lumens	
TP-FMR16-48LED-001 	MR16	48 LEDs	AC12V AC9-16V constant current	Warm White	2600-3700K	2W	30W	120 Lumens	
				Daylight White	5000-7000K		30W	120 Lumens	
TP-FGU10/E27/HR16-24LED-001 	GU10/E27/HR16	24 LEDs	AC12V AC110V AC230V	Warm White	2600-3700K	1.2W	25W	60 Lumens	
				Daylight White	5000-7000K		25W	60 Lumens	
TP-FGU10/E27/HR16-48LED-001 	GU10/E27/HR16	48 LEDs	AC12V AC110V AC230V	Warm White	2600-3700K	2W	30W	120 Lumens	
				Daylight White	5000-7000K		30W	120 Lumens	
TP-FRAE-24LED-001 	E27	24 LEDs	AC 12V AC110V AC230V	Warm White	Tc:2700-3700K	1.2W	25W	60 Lumens	
				Daylight White	Tc:5000-7000K		25W	60 Lumens	
TP-FRAE-36LED-001 	E27	36 LEDs	AC 12V AC110V AC230V	Warm White	Tc:2700-3700K	1.8W	30W	100 Lumens	
				Daylight White	Tc:5000-7000K		30W	100 Lumens	

Features:

- Certificate: FCC, CE, RoHS
- Energy-saving
- Longer Life than ordinary bulb(5 years)
- Solid State, High Shock/Vibration Resistant
- No UV, No RF Interference, Mercury Free
- Moisture-proof.
- Rated to Operate from -40°C to 45°C, Perfect for Environments with Extreme Climates